

RECEIVED
CENTRAL FAX CENTER

APR 20 2007

Application No. 10/695272
Response to Office Action dated 10/03/2006Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1 - 4. (Canceled)

5. (Withdrawn and Currently Amended) A display device comprising:

a simple matrix display provided with a plurality of signal electrodes and a plurality of scanning electrodes which are orthogonal to each other with an electrostatic capacity coupling display unit interposed therebetween;

a scanning side driving portion for sequentially scanning the scanning electrodes and supplying a scanning voltage; and

a signal side driving portion for supplying a pulse width modulation (PWM) PWM signal voltage to be a forward approach PWM signal voltage or a rearward approach PWM signal voltage to each of the signal electrodes synchronously with the scan of the scanning side driving portion,

wherein the signal side driving portion controls the PWM signal voltage in such a manner that ~~numbers of the forward approach PWM signal voltages and the rearward approach PWM signal voltages are almost equal to each other within a predetermined period for each of the scanning electrodes~~ the rearward approach PWM signal voltage is applied to the odd-numbered signal electrodes and the forward approach PWM signal voltage is applied to the even-numbered signal electrodes in a rearward/forward approach combination.

and the forward approach PWM signal voltage is applied to the odd-numbered signal electrodes and the rearward approach PWM signal voltage is applied to the even-numbered signal electrodes in a forward/rearward approach combination.

wherein said rearward/forward approach combination and said forward/rearward approach combination are switched at every predetermined frame cycle by a PWM signal controller.

Application No. 10/695272
Response to Office Action dated 10/03/2006

6. (Canceled)

7. (Canceled)

8. (Withdrawn and Currently Amended) The display device according to claim 5, wherein the signal side driving portion and the scanning side driving portion are configured to synchronize and alternate the PWM signal voltages applied to the signal electrode of the interposed display unit and a scanning voltage applied to the scanning electrode of the interposed display unit to have a predetermined relationship ~~with~~ within a frame cycle.

9. (Withdrawn and Currently Amended) A display driving method of a simple matrix display for performing a pulse width modulation (PWM) control, the method comprising the steps of:

applying a forward approach PWM signal voltage and a rearward approach PWM signal voltage to signal electrodes; and

sequentially scanning predetermined scanning electrodes such that a number of signal electrodes to which the forward approach PWM signal voltage is applied and a number of signal electrodes to which the rearward approach PWM signal voltage is applied ~~are set to be almost equal to each other~~ such that for each scanning period in which scanning electrodes are sequentially scanned, noise voltages generated by rise or fall of the PWM signal voltages cancel each other, and

wherein the PWM signal voltage is applied to have a rearward/forward approach combination in which the rearward approach PWM signal voltage is applied to an odd-numbered signal electrode and the forward approach PWM signal voltage is applied to an even-numbered signal electrode,

and wherein the PWM signal voltage is applied to have a forward/rearward approach combination in which the forward approach PWM signal voltage is applied to the odd-numbered signal electrode and the rearward approach PWM signal voltage is applied to the even-numbered signal electrode, and further

Application No. 10/695272
Response to Office Action dated 10/03/2006

wherein the rearward/forward approach combination and the forward/rearward approach combination are switched at every predetermined frame cycle.

10. (Canceled)

11. (Canceled)

12. (Withdrawn and Currently Amended) The display driving method according to claim 9, ~~wherein the steps of applying a forward approach PWM signal voltage and a rearward approach PWM signal voltage to the signal electrodes and sequentially scanning predetermined scanning electrodes comprises further comprising synchronously~~ alternating ~~synchronously~~ each of the PWM signal voltages and a scanning voltage applied to the scanning electrode to have a predetermined relationship ~~with~~ within a frame cycle.

13. (Withdrawn and Currently Amended) A display device comprising:

a simple matrix display provided with a plurality of signal electrodes and a plurality of scanning electrodes which are orthogonal to each other with an electrostatic capacity coupling display unit interposed therebetween;

a scanning side driving portion for sequentially scanning the scanning electrodes and supplying a scanning voltage; and

a signal side driving portion for supplying a PWM pulse width modulation (PWM) signal voltage to be a forward approach PWM signal voltage or a rearward approach PWM signal voltage to each of the signal electrodes synchronously with the scan of the scanning side driving portion,

wherein the signal side driving portion is configured to apply the forward approach PWM signal voltage to ~~an almost half~~ number of signal electrodes and further to apply the rearward approach PWM signal voltage to the residual signal electrodes for each scanning period in which the scanning electrodes are sequentially scanned to alternate between a rearward/forward approach combination and a forward/rearward combination

Application No. 10/695272
Response to Office Action dated 10/03/2006

in which the rearward/forward approach combination is characterized by the rearward approach PWM signal voltage being applied to the residual signal electrodes and the forward approach PWM signal voltage is applied to the even-numbered signal electrodes, and

the forward/rearward approach combination is characterized by the forward approach PWM signal voltage being applied to the odd-numbered signal electrodes electrode and the rearward approach PWM signal voltage is applied to the even-numbered signal electrode.

14. (Canceled)

15. (Withdrawn and Currently Amended) A display device, comprising
a single matrix display provided with a plurality of signal electrodes and a plurality of scanning electrodes which are orthogonal to each other with an electrostatic capacity couple display unit interposed therebetween;

a scanning side driving portion for sequentially scanning the scanning electrodes and supplying a scanning voltage; and

a signal side driving portion for supplying a PWM pulse width modulation (PWM) signal voltage to be a forward approach PWM signal voltage or a rearward approach PWM signal voltage to each of the signal electrodes synchronously with the scan of the scanning side driving portion, wherein the signal side driving portion is configured to apply the PWM signal to have a rearward/forward approach combination in which the rearward approach PWM signal voltage is applied to an odd-numbered scanning signal electrode and the forward approach PWM signal voltage is applied to an even-numbered scanning signal electrode or a forward/rearward approach combination in which the forward approach PWM signal voltage is applied to the odd-numbered scanning signal electrode and the rearward approach PWM signal voltage is applied to the even-numbered scanning signal electrode.

16. (Withdrawn and Currently Amended) The display device according to ~~a claim 13,~~ claim 15, wherein the signal side driving portion and the scanning side driving portion

Application No. 10/695272
Response to Office Action dated 10/03/2006

synchronize and alternate the rearward/forward approach combination with the forward/rearward approach combination to apply the PWM signal voltage voltages and a scanning voltage to be applied to the scanning electrode ~~to have~~ in a predetermined relationship ~~with~~ within a frame cycle.

17. (New) A method of providing signals to drive a plurality of pixels arranged in a simple matrix display, the method comprising the steps of:

switching between a rearward/forward combination approach and a forward/rearward combination approach in every frame cycle,

wherein the rearward/forward combination approach comprises applying rearward pulse width modulation (PWM) signals to the pixels corresponding to a plurality of odd-numbered scanning electrodes and applying forward PWM signals to the pixels corresponding to a plurality of even-numbered scanning electrodes, and

the forward/rearward approach comprises applying the forward PWM signals to the pixels corresponding to the odd-numbered scanning electrodes and applying the rearwards PWM signals to the pixels corresponding to the even numbered scanning electrodes.

18. (New) The method of providing signals to drive a simple matrix display according to claim 17, further comprising applying and synchronously switching the PWM signals and the scanning voltage to each pixel in a predetermined relationship within the frame cycle.

19. (New) A display device comprising:

a simple matrix having a plurality of signal electrodes, a plurality of scanning electrodes and a plurality of pixels corresponding to the intersections between said signal electrodes and said scanning electrodes;

a scanning side driving portion arranged to sequentially supply said scanning electrodes with a scanning voltage signal; and

a signal side driving portion to supply said signal electrodes with rearward approach PWM signals and forward approach PWM signals synchronously with the

Application No. 10/695272
Response to Office Action dated 10/03/2006

scanning voltage signal, said signal side driving portion including a PWM signal controller arranged:

to apply the rearward approach PWM signals to said pixels corresponding to odd-numbered scanning electrodes and the forward approach PWM signals to said pixels corresponding to the even-numbered scanning electrodes in a rearward/forward approach combination, and

to apply the forward approach PWM signals to said pixels corresponding to the odd-numbered scanning electrodes and the rearward approach PWM signals to said pixels corresponding to the even-numbered scanning electrodes in a forward/rearward approach combination,

wherein said rearward/forward approach combination and said forward/rearward approach combination are switched every frame cycle by said PWM signal controller.